

Single Door Entrance Systems

Fiber-Classic® Fiberglass Entry Door Systems



FC106

Few doors stand the test of time like a beautiful Fiber-Classic® entryway. It's the industry's original fiberglass door, engineered with the look and feel of a natural wood door.

The designs shown in the Big L Distributors Therma Tru Fiber-Classic® Selection guide represent the most popular selections from each of the Therma-Tru Fiber-Classic® glass and panel collections.

The pricing shown below each design is for the following specification:

- 30", 32", 34" or 36" x 80" or 84" nominal size unpainted, unstained Fiber-Classic® doors. Specific design size availability as noted. Therma Tru Finishing Kit not included.
- Rough opening sizes of 32-1/2" (30" door), 34-1/2" (32" door), 36-1/2" (34" door) or 38-1/2" (36" door), x 82-1/2" or 86-1/2"
- The unit is prehung with (3) brasstone self-aligning hinges in a 4-9/16" weather-stripped prime painted Frame-Defense® wood jamb, the door and jamb are prepped for lockset and deadbolt, a Tru-Defense aluminum sill with composite substrate and adjustable riser with a protective sill cover applied, adjustable security strike plate, and exterior brickmould casing.
- Prices do not include sales tax, locksets, delivery charges, or installation.

Prices and availability are subject to change without notice and are intended to give you a general guide to a broad range of design choices. Your final price may vary depending on jamb specifications, and hardware and sill options. Please call us at 800-336-2445 to get an exact detailed quotation, including installation.

For the complete selection of Therma Tru Doors, visit www.thermtru.com.



Polyurethane Foam Core. Offers five times the energy efficiency of a wood door and is CFC-free.



Our BTS doorlite frames stand up to temperature extremes.




Polystyrene doorlite frames warp and turn yellow over time.



Weatherstrip. Foam-filled compression weather-stripping remains flexible and seals your entrance against moisture and air infiltration.

Exclusive Doorlite Frames. BTS Doorlite frames handle temperature swings and extremes without warping, splitting, cracking, or yellowing – even behind storm doors where thermal heat buildup occurs. You can stain or paint Therma Tru doors a dark color without worry, or compromising the warranty.



Tru-Defense Sills.. High Dam design with composite threshold cap locks under the door while a flush surface provides full contact between the sweep and sill to keep water out.



Kerfed Door bottom. Provides a tight seal. Composite top and bottom rails won't rot or warp.



Tru-Defense Corner Seal pad. It's innovative design creates a pocket that effectively prevents water infiltration.



Tru-Defense Door Bottom Sweep. Features dual bulbs with dual fins that sit tightly on the sill to help prevent air and water infiltration.

**GUARD
AGAINST
ATTACK**

Frame Defense Limited Lifetime Warranty Exterior Door Frames

Frame Defense provides an effective method of controlling moisture using a combination of a high quality primer with a specially formulated end grain seal to create an advanced moisture barrier

